

Tyres

GAZELLE

- Ultralight
- Kevlar bead wire (foldable)
- Dual layer for very high puncture resistance
- Protection belt width: 15 mm
- Puncture resistant material: tightly weaved nylon fabric (named SPL) provides an extraordinary high level of puncture resistance.
- Carcass 127 TPI
- Minimum rolling resistance
- Psi: 85-145, recommended 110
- Bar: 6.0-10.0, recommended 7.5
- Max load 70 kg



Size	ETRTO	Weight approx. g	Part no.
24" x 1"	23-540	195 g +/- 10 g	41240A
25" x 1"	23-559	200 g +/- 10 g	41250A

SPEEDLITE

- Steel bead wire
- Dual layer for very high puncture resistance
- Protection belt width: 15 mm
- The main material used for the protection belt is natural rubber (named PTR) and is exceptionally puncture resistant.
- Carcass 67 TPI
- Low rolling resistance
- Psi: 85-145, recommended 110
- Bar: 6.0-10.0, recommended 7.5
- Max load 70 kg



Size	ETRTO	Weight approx. g	Part no.
20" x 1"	25-451	245 (+/- 15 g)	41200B
22" x 1"	25-489	260 (+/- 15 g)	41220B
22" x 1"	25-501	265 (+/- 15 g)	41220BL
24" x 1"	25-540	265 (+/- 15 g)	41240B
25" x 1"	25-559	280 (+/- 15 g)	41250B
26" x 1"	25-590	300 (+/- 15 g)	41260B